ENFORCER®

Security

Wide Track-Mount Overhead-Door Magnetic Contact

SM-4201-LWQ *3" (76mm) Gap, SPST, Closed Loop, 36" Armored cable, 2 Wires*
Adjustable for door-channel widths 2⅝"~4" (66~101 mm)

Features

- 3" (76mm) Gap for overhead doors in both industrial and residential situations where a wide gap is present
- Adjustable to fit most door-channel widths
- Rugged aluminum housing, IP65 weatherproof
- 36" (91cm) Wire leads enclosed in armored cable
- Contact type: iridium-plated to have a high melting point and Vickers hardness for higher power handling and longer expected life
- SPST closed loop circuits
- Mounting bracket included
- Lifetime limited warranty



SM-4201-LWQ

LIMITED LIFETIME WARRANTY | Iridium-Plated Contacts | Door Channel Width 2⅝"~4" | 36" Armored Cable | 3" Gap

Specifications

Loop type		Closed
Electrical configuration		N.O. (SPST)
Wires		2
Operation gap		3" (76mm)
Connectors		36" (91cm) Armored leads
Material	**Case**	Aluminum
	Contacts	Iridium-plated
Contact rating		1.0A@10VDC (max.)
		10W (max.)
Door channel width		2⅝"~4" (66~101 mm)
Switch cycles		50 Million (0.1mA@5VDC)
IP Rating		IP65 Weatherproof
Operating temperature		-15°~160° F (-25°~70° C)
Dimensions	**Switch**	3⅛"x2⅝"x1 13/16" (79x66x46 mm)
	Magnet	3¼"x3 9/16"x1¾" (82x90x44 mm)
Magnet type		Ferrite

Also Available from SECO-LARM

Track-Mount Overhead-Door Magnetic Contacts



SM-4201-LQ
SPST, Closed Loop
SM-4201-L3Q
SPDT, Open/Closed Loop
SM-4201-L6Q
DPDT, Open/Closed Loop

SECO-LARM® U.S.A., Inc.
16842 Millikan Avenue, Irvine, CA 92606
Phone: (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326
Website: www.seco-larm.com **Email:** sales@seco-larm.com

RoHS

Copyright © 2025 SECO-LARM U.S.A, Inc. All rights reserved.
All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.
SECO-LARM® ENFORCER® CRIMEBUSTER® CBA® SLI® AE®

Contacto Magnético para Puerta Superior con Montaje en Riel Ancho

SM-4201-LWQ *Separación de 3" (76 mm), SPST, circuito cerrado, cable blindado de 36", 2 hilos*
Ajustable para anchos de canal de puerta de 2⅝" a 4" (66 a 101 mm)

Características

- Separación de 3" (76 mm) para puertas superiores en entornos industriales y residenciales donde existe una separación amplia
- Ajustable para adaptarse a la mayoría de los anchos de canal de puerta
- Carcasa de aluminio resistente, impermeable IP65
- Cables de 36" (91 cm) protegidos con cable blindado
- Tipo de contacto: chapado en iridio para ofrecer un alto punto de fusión y dureza Vickers, lo que permite manejar mayor potencia y una vida útil más prolongada
- Circuitos SPST de bucle cerrado
- Incluye soporte de montaje
- Garantía limitada de por vida



SM-4201-LWQ

LIMITED LIFETIME WARRANTY

Contactos Chapados en Iridio

Ancho del canal de la puerta 2⅝"~4"

36" Cable Blindados

Brecha de 3"

Especificaciones

Tipo de circuito		Cerrado
Configuración eléctrica		N.A. (SPST)
Cables		2
Brecha de operación		3" (76mm)
Connectores		36" (91cm) Cables blindados
Material	**Caja**	Aluminio
	Contactos	Chapado en iridio
Puntuación de contactos		1.0A@10V C.C. (max.)
		10W (max.)
Ancho del canal de la puerta		2⅝"~4" (66~101 mm)
Ciclos de conmutación		50 Milliones (0.1mA@5V C. C.)
Clasificación IP		IP65 Resistente a la intemperie
Temperatura		-15°~160° F (-25°~70° C)
Dimensiones	**Interruptor**	3 1/8"x2 5/8"x1 13/16" (79x66x46 mm)
	Imán	3 1/4"x3 9/16"x1 3/4" (82x90x44 mm)
Tipo de imán		Ferrite

También disponible en SECO-LARM

Contactos magnéticos para puertas superiores con montaje en riel



SM-4201-LQ
SPST, circuito cerrado

SM-4201-L3Q
SPDT, circuito abierto/cerrado

SM-4201-L6Q
DPDT, circuito abierto/cerrado

SECO-LARM® U.S.A., Inc.
16842 Millikan Avenue, Irvine, CA 92606
Phone: (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326
Website: www.seco-larm.com **Email:** sales@seco-larm.com

Copyright © 2025 SECO-LARM U.S.A, Inc. Todos los derechos reservados.
Todas la marcas comerciales son propiedad de SECO-LARM U.S.A., Inc. o sus respectivos propietarios.
La póliza de SECO-LARM es de desarrollo y mejora continua. Por esa razón, SECO-LARM se reserva el derecho de cambiar las especificaciones y los precios sin previo aviso. SECO-LARM tampoco es responsable de errores de impresión.
SECO-LARM® ENFORCER® CRIMEBUSTER® CBA® SLI® AE®